



15', 20',
24' &
25'

**Precision
Three-Point**



The Three-Point Precision Seeding Systems™ from Great Plains feature the SingulatorPlus™ Meter mounted on the row unit close to the ground for extremely accurate placement of seed. It's a unique system that provides early canopy, uniform plant spacing and moisture saving characteristics of narrow rows. All of this in a system featuring seed singulation and plant spacing previously available only on traditional wide row planters.

Looking to change row widths? Switching row spacing from 7-1/2" to 15" to 30" to Twin Row 30" or 10" to 20" to 30" is as easy as removing a pin and shutting off the desired rows. A full line-up of meter wheels enables you to quickly switch from singulating soybeans, corn, cotton or milo to volumetrically metering wheat or rice. If you're looking for a truly versatile planting system... look no further.

Features

Features

Opener Features
Planter Style Sprocket Box
Weatherproof Lids
Seed level indicator
V-Bottom Dividers

Singulator-Plus
Telescoping SeedTube
Acremeter
Walkboard and Ladder
Safety Lighting Package

Options

Options

Press Wheels
Seed Box Agitator
Small Seeds Box *
Precision Meter Wheels
Baffles

Population Monitors
Variable Rate Drive
Microband
Seed Tube Plugs
Markers

*Available on 15', 20' only with 10P or 20P series openers only

Opener Options

Openers

10 Series Precision
20 Series Precision
15 Series Precision

15', 20', 24' & 25' Precision Three-Point Specifications

Model Name	1510P, 1520P			2010P, 2015P, 2020P			2410P, 2420P			2515P
Row Spacing	7 1/2"	10"	15"	7 1/2"	10"	15"	7 1/2"	10"	15"	15"
Number of Openers	24	18	12	32	24	16	38	28	20	20
Weight	4870, 5550 lbs.			5310, 7200, 6880 lbs.			6066, 7831 lbs.			8940 lbs.
Working Width	15'			20'			24'			25'
Transport Width	15' 4"			20' 2"			24' 2"			25' 2"
Transport Clearance	1' 5**			1' 5**			1' 5**			1' 5**
Height	5' 11"			5' 11"			5' 11"			5' 11"
Length	N/A			N/A			N/A			N/A
Seed Box Capacity	36 bu.			48 bu.			57 bu.			58 bu.
Tire Size	9.5" x 15, 11" x 15"			9.5" x 15, 11" x 15"			Dual 11L x 15"			Dual 11L x 15"
Opener Travel	10"			10"			10"			10"
Opener Depth	0" to 3 1/2"			0" to 3 1/2"			0" to 3 1/2"			0" to 3 1/2"
Opener Down Pressure	10P Series - 100 lb. To 140 lb. 20P Series - 100 lb. To 225 lb.			10P Series - 100 lb. To 140 lb. 15P Series - 260 lb. To 530 lb. 20P Series - 100 lb. To 225 lb.			10P Series - 100 lb. To 140 lb. 20P Series - 100 lb. To 225 lb.			15P Series - 260 lb. To 530 lb.

*Note: Weights based on 7.5" spacing and will vary depending on options. Transport clearance will vary depending on tractor.

Drill Versus Planter Capacity

The Precision Seeding System™ provides planter accuracy with the seed capacity of a drill. The large 2.4 bu. seed boxes allow you to increase productivity by reducing the amount of time spent refilling boxes.



The Ultra-Narrow Row Unit™

The Ultra-Narrow Row Unit™ features the SingulatorPlus™ Meter mounted just above the seedbed to minimize seed drop. The exclusive design of the row unit makes singulating seed on rows as narrow as 7-1/2" possible.



Opener Options

Select from three of our Precision Ultra-Narrow Row Units™. Each designed to excel in different applications.

10 Series Singulating Opener Applications *

- Conventional
- Min-Till
- Narrow Row Spacing
- No-Till
- High Residue
- One Pass



20 Series Singulating Opener Applications *

- Conventional
- Min-Till
- Stale Seedbed
- Narrow Row Spacing



15 Series Singulating Opener Applications **

- Conventional
- Min-Till
- Stale Seedbed



* Not available on 25' model.

** Not available on 24" model.

