

# 1230 Gallon TRAILER SPRAYERS



The TSF-1260, TSF-1280 and TSF-1290 are our largest sprayers to date with 1230 gallons of onboard spraying capacity. The TSF-1260 is fitted with our rugged 60' wet boom for maneuverability and affordability. The TSF-1280 is equipped with a 80' boom that is convertible to 60' for spraying in hard to reach or rough terrain. The TSF-1290 is a 90' version that is also convertible to 60'. All 1230 gallon sprayers are equipped with super tall 14.9 x 46 radial tires for maximum flotation, yet narrow tread width for improved clearance between rows.

## MODELS

**TSF-1290**

**TSF-1280**

**TSF-1260**





## 1230 GALLON TRAILER SPRAYER SPECIFICATIONS



1230 Gallon Poly Tank




Heavy Duty Frame & Hitch



Walkboard & Ladder



Safety Lighting Package



Adjustable Axles



42" Cushioned Elevator



Central Control Panel



Electro/Hyd Controls



Wet Boom Plumbing



14.9 x 46 Radial Tires



Flush and Rinse Turrets

### FEATURES & BENEFITS

Feature	Benefit
1230 Gallon Poly Tank	High capacity for maximum field efficiency
Heavy Duty Frame and Hitch	Uniform load and more contact with the tank means longer tank life and durability
Walkboard and Ladder	Wide steel walkboard and folding steps allow easy, safe access to top of sprayer
Safety Lighting Package	Provides a high level of visibility and safety during transport
Adjustable Axles	Allows wheelbase changes to match crops and tractor (80" to 120")
42" Spring Cushioned Elevator	Elevator holds boom tighter eliminating the excess movement associated with parallel linkage
Central Control Panel	Puts all major sprayer operations at one location
Electro/Hyd. Boom Controls	Provide fingertip control of all boom function, controls seven functions with one hyd. outlet
Wet Boom Plumbing	Keeps pressure equal to all nozzles and minimizes trapped chemicals
14.9 x 46 Radial Tire Assembly	Provide maximum flotation and least compaction
Flush and Rinse	100 Gallon fresh water tank with 3 turret nozzles for quick and complete clean out

### OPTIONAL EQUIPMENT

3 Gallon Chemical Inductor	Raven 440 for use with Tractor Radar	Clevis or Single Tang Hitch
TS Ace 150 5/4 Drive Pump	TSF Wheel Sensor Kit	
TS Ace 1000 1-3/8 Drive Pump	TSF Radar Kit	
TS High Volume Hydraulic	25 Gallon Foam Marker	

### SPECIFICATIONS

Model Name	TSF1260	TSF1280	TSF1290
Boom Width	60'	80'	90'
Nozzle Spacing	20 or 30"	20 or 30"	20 or 30"
Capacity	1230 Gallons	1230 Gallons	1230 Gallons
Wheels	14.9 x 46 Radial	14.9 x 46 Radial	14.9 x 46 Radial
Wheel Spacing	80" to 120"	80" to 120"	80" to 120"
Pump Options	Ace Hydraulic/PTO	Ace Hydraulic/PTO	Ace Hydraulic/PTO
Pump Specs	90 GPM @30 PSI	90 GPM @30 PSI	90 GPM @30 PSI
Foam Marker	25 Gallon (optional)	25 Gallon (optional)	25 Gallon (optional)
3 Gal Chemical Inductor	(optional)	(optional)	(optional)
Flush & Rinse	100 Gallon	100 Gallon	100 Gallon
Height (transport)	13' 6"	13' 6"	13' 6"
Width (transport)	12'	12'	12'
Length	22' 5"	22' 5"	22' 5"
Ground Clearance	28"	28"	28"

Specifications subject to change without notice.

\*\*Transport clearance will vary depending on tractor.