

650 Gallon TRAILER SPRAYERS

from



MODEL TSF-660

The TSF-660 trailer sprayer is designed to be a more maneuverable alternative to our larger capacity machines whether in the field or on the road. The compact design of the TSF-660 makes it perfect for smaller more economical tractors yet in the field the TSF-660 still utilizes larger diameter tires to maximize flotation. The 60' boom folds to a narrow 108" wide making it safer and easier to transport than larger models. The 60' front fold boom has all the strength and features of the larger model booms, like wet boom plumbing, break away sections, and incredible balance and strength. The 60" to 120" adjustable axle allows for tires to be spaced to match any row width with superior stability.



Great Plains

650 GALLON TRAILER SPRAYER SPECIFICATIONS



650 Gallon Poly Tank




Heavy Duty Frame & Hitch



Walkboard & Ladder



Safety Lighting Package



Adjustable Axles



42" Cushioned Elevator



Central Control Panel



Electro/Hyd Controls



Wet Boom Plumbing



Boom Suspension



Flush and Rinse Turrets

FEATURES & BENEFITS

Feature	Benefit
650 Gallon Poly Tank	Can use a smaller tractor to pull and creates less compaction in the field
Heavy Duty Frame and Hitch	Uniform load and more contact with the tank means longer tank life and durability
Walkboard and Ladder	Wide steel walkboard and folding steps allow easy, safe access to top of sprayer
Safety Lighting Package	Provides a high level of visibility and safety during transport
Adjustable Axles	Allows wheelbase changes to match crops and tractor (60" - 120")
42" Spring Cushioned Elevator	Elevator holds boom tighter eliminating the excess movement associated with parallel linkage
Central Control Panel	Puts all major sprayer operations at one location
Electro/Hyd. Boom Controls	Provide Fingertip control of all boom function, controls seven functions with one hyd. outlet
Wet Boom Plumbing	Keeps pressure equal to all nozzles and minimizes trapped chemicals
Boom Suspension	Springs over shock design that provides suspension and unmatched boom stability
Flush and Rinse Turrets	50 Gallon fresh water tank with 2 turret nozzles for quick and complete clean out

OPTIONAL EQUIPMENT

3 Gallon Chemical Inductor	TSF Radar Kit
TSF Wheel Sensor Kit	25 Gallon Foam Marker

SPECIFICATIONS

Model Name	TSF660
Boom Width	60'
Nozzle Spacing	20" or 30"
Capacity	650 Gallons
Wheels	13.6 x 38 6 Ply
Wheel Spacing	60" to 120"
Pump Options	Ace Hydraulic
Pump Specs	90 GPM @30 PSI
Foam Marker	25 Gallon (optional)
3 Gal Chemical Inductor	(optional)
Flush & Rinse	50 Gallon
Height (transport)	12'
Width (transport)	108" (wheels in) 135" (wheels out)
Length	19' 10"
Ground Clearance	28"

Specifications subject to change without notice.
 **Transport clearance will vary depending on tractor.