

# 40' Heavy Duty No-Till DRILLS

from



The 3N-4010HDF drill is designed to meet the demands of today's large scale no-till farmers. These workhorses are built around the 10HD series "Heavy Duty" opener. The 10HD is the first opener available on 7.5 inch spacing that can have a coulters mounted directly to it. This feature allows the coulters depth to be set in direct proportion to the opener disc blades.

When faced with BT corn stalks or tangled wheat stubble, proper coulters depth management is a valuable asset. You can also choose to equip the drill with a spring loaded frame mount coulters which offers additional protection from stones. The 10HD may also be ordered without coulters to reduce soil disturbance and cost, but coulters can be added at anytime.


MODEL  
**3N-4010HDF**

For seed metering, it uses the simplicity of our proven 1 3/4" fluted feed cup, and comes standard with the Veris® hydraulic drive. This system allows on-the-go seed rate changes and is also fully G.P.S. compatible. This productive unit folds to a narrow 14' 10 1/2" width. All of the gauge wheels remain on the ground, keeping the unit stable and safe. This unit is also available as a 3N-4010HDP version that incorporates the ability to singulate corn, milo, soybeans and cotton into the 10HD opener.




# Great Plains

## 40' NO-TILL DRILL SPECIFICATIONS



Narrow Transport Width



Floating Tongue



Pivoting Gauge Wheels




Press Wheel Choices



Large Seed Boxes



Heavy Duty Springs



Short Pull-Bar Length



2 Coulters Options



1/2" Offset 15" Dia. Disc Blades



Planter Seed Tube



Skid Steer Tires

### FEATURES & BENEFITS

Feature	Benefit
Narrow Transport Width	Folds to a narrow 14' 10 1/2" for safe road travel
Heavy Duty Springs	Up to 500 lbs available for penetration
Short Pull-Bar Length	Allows for shorter end row turns, rigid design - no telescoping needed
2 Coulters Options	Coulters prepare a mini seedbed, unit mount or spring loaded frame mount available
1/2" Offset 15" Dia. Disc Blades	Increased offset allows easier penetration, 15" dia. blades improve trash cutting - 4mm thick blades last longer
Planter Seed Tube	Helps eliminate seed bounce which increases seed spacing accuracy.
Skid Steer Tires	Extra tough for strong bt corn stocks and soybean stubble, all 12 wheels help provide flotation in soft ground
Floating Tongue	Provides superior terrain following because unit pivots independently of the tongue
Pivoting Gauge Wheels	As unit folds gauge wheels move outboard and become leading transport wheels
Press Wheel Choices	Choose from 3 different press wheels to match your soil and seedbed conditions
Large Seed Boxes	2.4 bu. per foot seed boxes with wide lids and stable walkboard fill fast and keep you in the field longer

### OPTIONAL EQUIPMENT

Flat Fold Markers	Keeton Seed Firmers	Unit Mount Coulters
Liquid Fertilizer Kit	Weight Brackets	Seed-Lok® Wheels
Choice of Press Wheels	Fluted, Wavy or Turbo Blades	Frame Mounted Coulters
Seed Tube Plugs		

### SPECIFICATIONS

Model Name	3N-4010HDF
Row Spacing	7 1/2", 10"
Number of Openers	64, 48
Weight	29,540 lbs.*
Working Width	40'
Transport Width	14' 10 1/2"
Transport Clearance	13 1/2"
Height	8'
Seedbox Capacity	96 bu.
Tire Size	33 x 15.5 - 16.5
Opener Travel	10"
Opener Depth Settings	0" to 3 1/2"
Opener Down Pressure	235 to 500 lbs.
HP Requirements (est)	275 to 400

Note: All specifications subject to change without notice.

\*Weights based on 7.5" spacing and will vary depending on options.