

26' 2-Section FOLDING DRILL

from



MODEL
2S-2600

Once again, Great Plains has out-classed the competition. The 2S-2600 offers the small to medium sized operator the features and benefits of the 30' and 40' drills but with lower investment costs. Its 3.2-bushel per foot box allows it to be as productive as older 30' models with smaller seedboxes. Add convenient rate changes and minimal daily maintenance and you will agree that this is the most productive drill in its class.

The openers feature constant hydraulic down-pressure that allows you to independently adjust the down-pressure from the center to the outsides of the machine. If you want more down-pressure to help maintain consistent seed depth in the tractor tracks, just dial it in and leave the ends of the drill alone. This drill has the same 20° upward flex and 15° downward flex as the 30' and 40' models.



Great Plains

HYDRAULIC DOWN-PRESSURE DRILL SPECIFICATIONS



4-Speed Sprocketbox



By-Pass Valve



Walkboard and Ladder



Safety Lighting Package




1 3/4" wide Fluted Feed Cup



Independent Opener Travel



Weatherproof Lids



V-Bottom Dividers



In-Line Filter



Keeton or Seed-Lok®
Seed Firmers



Skid Steer Tires

FEATURES & BENEFITS

Feature	Benefit
4-Speed Sprocketbox	Provides excellent metering of a large variety of seed shapes and sizes.
By-Pass Valve	Reduces hydraulic oil heating.
Walkboard and Ladder	Wide non-skid walkboard and ladder provide easy access the full width of the machine.
Safety Lighting Package	Provides a high level of visibility and safety during transport.
Fluted Feed Cup	Provides gentle and even delivery of a wide variety of seed sizes and shapes.
Independent Opener Travel	Cylinders on both ends of each gang allow it to hug terrain independent of the drill box.
Weatherproof Lids	Hydraulic lid protects seed and fertilizer from the elements.
V-Bottom Dividers	Provide even and complete seedbox clean out.
In-line filter	Reduces oil contamination.
Keeton or Seed-Lok®	Firms soil creating excellent seed-to-soil contact. (Optional)
Skid Steer Tires	Provides greater flotation. (3 section models only) (Optional)

OPTIONAL EQUIPMENT

Press Wheels (pg. 5)	Markers	Keeton Seed Firmers
Seed Cup Plugs	Point-Row Clutches	Seed-Lok® Seed Firmers
Fertilizer Attachment	Shaft Monitors	Open Center Kit
Small Seeds Box	Skid Steer Tires (3000 & 4000 only)	Air Design Scrapers

SPECIFICATIONS

Model Name	2S-2600			3S-3000			3S-4000		
Row Spacing	6"	7 1/2"	10"	6"	7 1/2"	10"	6"	7 1/2"	10"
Number of Openers	52	42	32	60	48	36	78	63	48
Weight*	11760 lbs.			11890 lbs.			17600 lbs.		
Working Width	26'			30'			40'		
Transport Width	15'			15'			15'		
Transport Clearance**	1' 5"			1' 5"			1' 5"		
Height	8' 2"			8' 2"			7' 4"		
Length	26' 4"			30'			34' 8"		
Seedbox Capacity	86.4 bu.			97.2 bu.			128 bu.		
Seed/Fertilizer Capacity	See pg. 7			See pg. 7			See pg. 7		
Tire Size Std.	11" x 15" w/ 9.5" x 15"			11" x 15" w/ 9.5" x 15"			11" x 15" w/ 9.5" x 15"		
Optional Skid Steer	N.A.			10" x 16.5" w/ 10" x 16.5"			15" x 16.5" w/ 10" x 16.5"		
Opener Travel	8"			8"			8"		
Opener Depth	0" to 3 1/2"			0" to 3 1/2"			0" to 3 1/2"		
Opener Down-Pressure	90 lb. To 180 lb.			90 lb. To 180 lb.			90 lb. To 180 lb.		
HP Requirements (est.)	110 min.			125 min.			180 min.		

*Note: Weights based on 7.5" spacing and will vary depending on options.

**Transport clearance will vary depending on tractor.