

12', 15', 20' 3-Point DRILLS



As seeding specialists, we recognize the need for different openers to match specific farming practices. Great Plains offers three openers to assure accurate seed placement in widely varying field conditions. Combine our opener options with superior construction and innovative engineering and you'll quickly realize the advantages of a Great Plains 3-Point Drill.

Choose between the "00" series straight-arm opener (standard) or the "10" series parallel linkage opener that features more travel and more control of precise contact angle. You can also choose the "20" series parallel linkage opener with side depth controlling wheels – this row unit utilizes 2" x 13" side depth wheels which provide excellent depth control in min-till and conventional conditions. These side depth wheels also help prevent trench blowout in heavy gumbo type soils

MODELS
1200
1500, 1510
3PNG12
3PNG15
2000, 2010, 2020



"00"



"10"



"20"

NATIVE GRASS DRILL



SEED FORWARD BOX DESIGN



Our seed forward box design boasts 2.4 bushel-per-foot capacity. A main seedbox agitator can be included as optional equipment. Single tube 6" x 6" mainframe provides the structural soundness for which Great Plains is noted.

Great Plains has designed 2 models of 3-Point Drills specifically for the seeding of native grasses. The 3PNG12 and 3PNG15 combine the "00" series opener with our proven native grass attachment. They come standard with a 2 bushel per foot fluted seedbox and a 1 cu. ft. per foot native grass box. Add a Center Pivot Hitch or Precision Fertilizer Hitch to enhance its no-till seeding capabilities.

Great Plains

12', 15', 20' 3-POINT DRILL SPECIFICATIONS



4-Speed Gearbox



Acrometer



Walkboard and Ladder




Safety Lighting Package




Fluted Feed Cup



Weatherproof Lids



V-Bottom Dividers



Seed Level Indicator



Fertilizer Attachment



Small Seeds Box



Flat Fold Markers

FEATURES & BENEFITS

Feature	Benefit
4-Speed Gearbox	Gears rotate free from dust and dirt for smooth operation and a long wear life. (except NG)
Acrometer	Precise meter accurately keeps track of the acres covered.
Walkboard and Ladder	Wide non-skid walkboard and ladder provide easy access the full width of the machine.
Safety Lighting Package	Provides a high level of visibility and safety during transport.
Fluted Feed Cup	Provides gentle and even delivery of a wide variety of seed sizes and shapes.
Weatherproof Lids	Hydraulic lid protects seed and fertilizer from the elements.
V-Bottom Dividers	Provide even and complete seedbox clean out.
Seed Level Indicator	High visibility seed level indicator can be easily viewed from the cab.
Fertilizer Attachment	Easy cleanout and 6 point meter wheels that accurately meter fertilizer.
Small Seeds Box	Smaller version of the fluted feed cup accurately meters small seeds.
Flat Fold Markers	Heavy duty markers are strong enough to penetrate tough conditions.

OPTIONAL EQUIPMENT

Press Wheels (pg. 5)	Fertilizer Attachment	Markers
Fluted Seed Cup Plugs	Small Seeds Box	Seedbox Agitator (except native grass)

SPECIFICATIONS

Model Name	1200, 3PNG12					1500, 1510, 3PNG15					2000, 2010, 2020				
	6"	7"	7 1/2"	8"	10"	6"	7"	7 1/2"	8"	10"	6"	7"	7 1/2"	8"	10"
Row Spacing	6"	7"	7 1/2"	8"	10"	6"	7"	7 1/2"	8"	10"	6"	7"	7 1/2"	8"	10"
Number of Openers	24	20	19	18	14	30	26	24	22	18	40	34	32	30	24
Weight*	2659, 2650 lbs.					3213, 3645, 3200 lbs.					4300, 4676, 6316 lbs.				
Working Width	12'					15'					20'				
Transport Width	12'					15'					20'				
Transport Clearance**	1' 5"					1' 5"					1' 5"				
Height	8' 4"					8' 4"					8' 4"				
Length	NA					NA					NA				
Seedbox Capacity	28.8 bu., 24 bu.					36 bu., 36 bu., 30 bu.					48 bu., 48 bu., 48 bu.				
Tire Size	9.5" x 15"					9.5" x 15"					11" x 15"				
Opener Travel	6 1/2"					6 1/2"					6 1/2"				
Opener Depth	0" to 3 1/2"					0" to 3 1/2"					0" to 3 1/2"				
Opener Down-Pressure	00 Series - 90 lb. To 180 lb.					00 Series - 90 lb. To 180 lb. 10 Series - 100 lb. To 140 lb.					00 Series - 90 lb. To 180 lb. 10 Series - 100 lb. To 140 lb. 20 Series - 100 lb. To 225 lb.				

*Note: Weights based on 7.5" spacing and will vary depending on options.

**Transport clearance will vary depending on tractor.