



• Photo may show optional equipment not supplied with standard unit.

We challenge you to find a no-till seeding system in a 20' working width that can compare to the productivity of our 20' No-Till Air Drill. The 80 bushel seed box utilizes the efficiency of an air delivery system to deliver seed to the proven double disk openers, in conjunction with our narrow transport width maximizing productivity while minimizing fill times.

Great Plains exclusive CPH (Center Pivot Hitch) is the only no-till system that tracks properly on curves and contours. The CPH ensures the openers are aligned with the corresponding coulter. Only Great Plains features a pivot point positioned exactly between the coulters and row openers... the key to proper tracking.

Features

- Features
- High Capacity Fan
- Wide Steel Walkboard
- Opener Features
- Transport Lights

Options

- | | |
|------------------|---------------------------|
| Options | Seed-Lok® |
| Small Seeds | Air Design® Disk Scrapers |
| Marker | Press Wheel Options |
| Monitors | Coulter Options |
| Coil Tine Harrow | |

Opener Options

- Openers
- 00 Series

20' No-Till Air Drill Specifications

Model Name	NTA2000	
Row Spacing	7.5" (19.05cm)	10" (25.40cm)
Number of Openers	32	24
Weight	16446lbs (7460kg)	
Working Width	20' (6.1m)	
Transport Width	10' (3m)	
Transport Clearance	16" (40cm)	
Height	11' (3.35m)	
Length	25' 4" (7.7m)	
Seed Box Capacity	80bu	
Tire Size	400/60-15.5	
Opener Travel	6.5" (16.51cm)	
Opener Depth	0 to 3.5" (0 to 8.89cm)	
Opener Down Pressure	90-180lbs (40.82 to 81.64kg)	
Coulter Depth	0 to 6" (0 to 15.24cm)	
Coulter Pre-load	450lbs (203kg)	

Note: Weights will vary depending on options. Transport clearance will vary depending on tractor.

Contact Drive

The dual Contact Drive is simple yet reliable. It incorporates a spring loaded shock absorber to keep positive contact with the gauge wheel.



Infinite Ratio Gearbox

Setting seed rates are made easy by adjusting the infinite ratio gearbox. This accurate gearbox allows you to return to previously checked rates without recalibration. The conveniently located tray and crank provide simple calibration and easy cleanout of the hopper.



10' Transport Width

The 20' No-Till Air Drill hydraulically folds to a narrow 10' transport width. Heavy duty transport tires provide a stable safe ride.



Center Pivot Hitch

Great Plains is the only no-till drill that plants properly on curves and contours. Our CPH (Center Pivot Hitch) aligns the coulters with the corresponding opener for perfect tracking.

